

Upgrade Your Toilet with a smarter one

HUIDA

Add a HUIDA intelligent toilet in your bathroom and experience how technology can change your life

| Item No. | | HDE7001T |
|--------------------------------|---------------------------|---|
| Rated Voltage | | 220V (Other voltages can be customized) |
| Rated Frequency | | 50Hz |
| rated power | | 1200W |
| Ambient Operating Temperature | | 4°C~40°C |
| Inlet Water Temperature | | 4°C~35°C |
| Operating Water Pressure Range | | 0.07MPa~0.75MPa |
| Cleaning | Warm Water Heating Mode | Instant Heating Mode |
| | Rear Water Output | 0.5~0.7L/min(5Levels) |
| | Front Water Output | 0.5~0.7L/min (5Levels) |
| | Warm Water Temperature | 34°C~40°C (4Levels) |
| Warm Air | Warm Air Temperature | 35°C~55°C (4Levels) |
| | Warm Air Speed | 4m/s |
| | Safety Device | Bimetallic Thermostat, ThermalCutoff Fuse |
| Seat Ring | Seat Cover/Ring Slow Down | 3s~60s |
| | Seat Ring Temperature | 28°C~40°C (4Levels) |
| | Safety Device | Thermal Cutoff Fuse |
| Fireproofing Grade | | V0 |
| Waterproof Grade | | IPX4 |
| Power Line Length | | 1.5m (customization is available) |
| Product Size | | 685mmx396mmx540mm |
| Product Weight | | ≈55KG |



Functional characteristics:

1. Zero water pressure flushing, 3.8 liters of water, first-level water effect, no noise;
2. 360 degree knob control;
3. large air drying: 1.5 minutes dry;
4. automatic sensor cover, foot touch cover, etc.;
5. Replaceable nozzle design;
6. LED digital display function;
7. Quick response of cleaning system;
8. Medical ultraviolet spray rod sterilization;
9. hot and cold massage cleaning;
10. Dual water quality filtration;
11. 900CC large flow frequency conversion heat transfer;